## Classic Perimeter Benches – Cloakroom Seating Manufactured by:



*ESE Direct Ltd*, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE Telephone: 01603 629956 – Fax: 01603 630113 – Email: <u>sales@esedirect.co.uk</u> Website: www.benchura.co.uk

N10 - Specification:



## 'BBL...' - Classic Mezzo Changing Bench:

| Dimensions:     | 325mm deep x 450mm seat height         |  |                    |
|-----------------|--|--|--------------------|
| Standard sizes: | 1m (2 sets legs)<br>2.5m (4 sets legs) | - 1.5m (3 sets legs)<br>- 3m (4 sets legs) | - 2m (3 sets legs) |

*Leg frames:* BBL - Constructed of 30mm x 30mm box section with floor fixing cleats (floor fixings not included), 300mm deep with 70mm wide top plate pre drilled (6 holes) ready to take 3 seat slats, ground and polished then powder coated to finish.

*Seat slats:* Ash heartwood - Consists of 3x 75mm x 25mm hardwood seat slats sanded and lacquered with sufficient screws supplied to fix slats to the legs.

## FINISH:

**Colours:** Stocked in Silver (Gloss) and also available in 5 additional colours - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Grey (BS18B25) - Black (RAL9005).

Ash hardwood slats: Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

**Steel legs and seat support frames:** Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

**Pre Zinc coating:** If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Pre Zinc Coating (additional cost applicable).

<u>Note:</u> For high humidity, regularly wet areas, external or pool side applications we would recommend our Stainless Steel range.