

**Classic Perimeter Benches** – Cloakroom Seating Manufactured by:

**Benchura**

*ESE Direct Ltd*, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE

Telephone: 01603 629956 – Fax: 01603 630113 – Email: [sales@esedirect.co.uk](mailto:sales@esedirect.co.uk)

Website: [www.benchura.co.uk](http://www.benchura.co.uk)

N10 - Specification:



'BML...' - Classic Mono Changing Bench:

Dimensions: 350mm deep x 450mm seat height

Standard sizes: 1m (2 sets legs) - 1.5m (3 sets legs) - 2m (3 sets legs)  
2.5m (4 sets legs) - 3m (4 sets legs)

**Leg frames:** **BML** - Constructed of 30mm x 30mm box section single leg with wall and floor fixing cleats (wall / floor fixings not included), 350mm deep with 70mm wide top plate pre drilled (6 holes) ready to take 3 seat slats, ground and polished then powder coated to finish.

**Seat slats:** Ash heartwood - Consists of 3x 75mm x 25mm hardwood seat slats sanded and lacquered with sufficient screws supplied to fix slats to the legs.

FINISH:

**Colours:** Stocked in Silver (Gloss) and also available in 5 additional colours - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Grey (BS18B25) - Black (RAL9005).

**Ash hardwood slats:** Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

**Steel legs and seat support frames:** Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

**Pre Zinc coating:** If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Pre Zinc Coating (additional cost applicable).

**Note:** For high humidity, regularly wet areas, external or pool side applications we would recommend our Stainless Steel range.