

Club Range Benches – Cloakroom Seating Manufactured by: 

*ESE Direct Ltd*, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE  
Telephone: 01603 629956 – Fax: 01603 630113 – Email: [sales@esedirect.co.uk](mailto:sales@esedirect.co.uk)  
Website: [www.benchura.co.uk](http://www.benchura.co.uk)

N10 - Specification:



'RD...X' - Club Round Frame Duo Cloakroom Bench Seat:

**Dimensions:** 800mm deep (385mm each side) x 1750mm high, seat 450mm high standard (Junior – Infant sizes available). 1m - 1.5m - 2m long or 2.5m - 3m long with a third upright in the centre.

**Leg frames:** Constructed of 45mm dia vertical tubes with 50mm x 30mm horizontal channels, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required) with plastic feet as standard. Available as options - Floor fixing cleats - Adjustable feet.

**Seats:** One per side constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 3x 75mm x 25mm Ash hardwood slats are factory fitted.

**Hat and Coat rail:** Constructed of 75mm x 25mm Ash hardwood to both sides of which Satin Anodised Aluminium two prong coat hooks are fitted.

1m = 10 hooks - 1.5m = 14 hooks - 2m = 20 hooks - 2.5m = 24 hooks - 3m = 28 hooks

OPTIONS:



**Shoe Racks:** Constructed using 6 powder coated round tubes (3 each side) and formed channel ends, simply bolts into the legs under the bench seat units at 150mm centres from the floor.



**Back Rests:** Constructed of 75mm x 25mm Ash hardwood rounded on all four edges and bolted to factory fitted steel mounting brackets on the uprights.

FINISH:

**Colours:** Available in a choice of 6 standard colours - Silver (Gloss) - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Green (RAL6009) - Black (RAL9005) - White (RAL9010) - Grey (BS18B25).

**Ash hardwood slats:** Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

**Steel / metal legs and seat support frames:** Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

**Zinc Plating:** If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

**Note:** For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.