

Club Range Benches – Cloakroom Seating Manufactured by: **Benchura**

ESE Direct Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE
Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@esedirect.co.uk
Website: www.benchura.co.uk



N10 - Specification:

'R5...' - Club Round Frame Mezzo Changing Room R5D Bench:

Dimensions: 500mm deep x 450mm high seat as standard (Junior – Infant sizes available).
1m - 1.5m - 2m long or 2.5m - 3m long with a third upright in the centre.
Designed to the Sport England and Football Foundation disability size guidelines.

Leg frames: Constructed of 45mm dia vertical tubes backset by 25mm from the front and rear of the seat to reduce risk of stubbing toes, with 50mm x 30mm horizontal channels, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required), with plastic feet as standard. Available as options - Floor fixing cleats - Adjustable feet.

Seat: Constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 5x 75mm x 25mm Ash hardwood slats are factory fitted.

OPTION:



Shoe Racks: Constructed using 3 powder coated round tubes and formed channel ends, simply bolts into the legs under the bench seat units at 150mm centres from the floor.

FINISH:

Colours: Available in a choice of 6 standard colours - Silver (Gloss) - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Green (RAL6009) - Black (RAL9005) - White (RAL9010) - Grey (BS18B25).

Ash hardwood slats: Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Zinc Plating: If the bench seats are for use in wet situations or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

Note: For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.