

Evolve Range Benches – Cloakroom Seating Manufactured by:

Benchura

ESE Direct Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE

Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@esedirect.co.uk

Website: www.benchura.co.uk



N10 - Specification:

'DS...M' - Evolve Duo Cloakroom Bench with Mesh top shelf:

Dimensions: 800mm deep x 1750mm high, 450mm high seat as standard (Junior – Infant sizes available). 1m - 1.5m - 2m or 2.5m - 3m long with a third upright.

Leg frames: Constructed of 30mm x 30mm box section with mitred joints, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required) with plastic feet as standard. Floor fixing cleats or adjustable feet available as options.

Seats: One per side constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 3x 75mm x 25mm Ash hardwood slats are factory fitted.

Mesh Top Shelf: Constructed using a powder coated 30x30 formed angle support framework into which 50mm x 25mm mesh is factory fitted, simply bolts into uprights of the leg frames.

Hat and Coat rail: Constructed of 75mm x 25mm Ash hardwood, both sides of which Satin Anodised Aluminium two prong coat hooks are fitted.
1m = 10 hooks - 1.5m = 14 hooks - 2m = 20 hooks - 2.5m = 24 hooks - 3m = 32 hooks

OPTIONS:



Mesh Shoe Racks: 30x30 formed angle support framework into which 50mm x 25mm mesh is fitted, simply bolts into the legs under the bench seat units at 150mm centres from the floor.

Back Rests: 70mm x 25mm Ash hardwood rounded on all four edges and bolted to steel mounting brackets on the uprights.

FINISH:

Colours: Available in a choice of 6 colours - Blue (RAL5002) - Silver (Gloss) - Yellow (RAL1018) - Red (RAL3020) - Grey (BS18B25) - Black (RAL9005).

Ash hardwood slats: Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Zinc Plating: If the bench seats are for use in wet conditions or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

Note: For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.