

Evolve Range Benches – Cloakroom Seating Manufactured by:

ESE Direct Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE
Telephone: 01603 629956 – Fax: 01603 630113 – Email: sales@esedirect.co.uk
Website: www.benchura.co.uk



N10 - Specification:

'BD...' - Evolve Mezzo Double Sided Changing Room Bench:

Dimensions: 595mm deep x 450mm high seat as standard (Junior – Infant sizes available).
1m - 1.5m - 2m or 2.5m - 3m long with a third upright in the centre.

Leg frames: Constructed of 30mm x 30mm box section with mitred joints, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required) with plastic feet as standard. Floor fixing cleats or adjustable feet available as options.

Seats: Constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 5x 75mm x 25mm Ash hardwood slats are factory fitted.

OPTION:



Mesh Shoe Racks: Constructed using a powder coated 30x30 formed angle support framework into which 50mm x 25mm mesh is fitted, simply bolts into the legs under the bench seat unit at 150mm centres from the floor.

FINISH:

Colours: Available in a choice of 6 colours - Blue (RAL5002) - Silver (Gloss) - Yellow (RAL1018) - Red (RAL3020) - Grey (BS18B25) - Black (RAL9005).

Ash hardwood slats: Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Zinc Plating: If the bench seats are for use in wet conditions or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

Note: For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.