Evolve Range Benches – Cloakroom Seating Manufactured by:



ESE Direct Ltd, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE Telephone: 01603 629956 – Fax: 01603 630113 – Email: <u>sales@esedirect.co.uk</u> Website: <u>www.benchura.co.uk</u>

N10 - Specification:



'M...' - Evolve Mono Changing Room Bench:

- Dimensions: 350mm deep x 450mm high seat as standard (Junior Infant sizes available). 1m - 1.5m - 2m or 2.5m - 3m long with a third upright in the centre.
- *Leg frames:* Constructed of 30mm x 30mm box section with mitred joints, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required) with floor and wall fitted fixing brackets.
- *Seats:* Constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 3x 75mm x 25mm Ash hardwood slats are factory fitted.

<u>OPTION:</u>



Mesh Shoe Racks: Constructed using a powder coated 30x30 formed angle support framework into which 50mm x 25mm mesh is fitted (complete with rear support brackets), simply bolts into the leg and under the bench seat unit at 150mm centres from the floor.

FINISH:

Colours: Available in a choice of 6 standard colours - Silver (Gloss) - Blue (RAL5002) - Yellow (RAL1018) - Red (RAL3020) - Grey (BS18B25) - Black (RAL9005).

Ash hardwood slats: Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

Steel / metal legs and seat support frames: Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

Zinc Plating: If the bench seats are for use in wet conditions or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

<u>Note:</u> For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.