

INSTRUCTIONS FOR: MOTORCYCLE RAMP 200KG CAPACITY MODEL No: MR200

Thank you for purchasing a Sealey Jack. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT: READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS JACK CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY, AND WILL INVALIDATE THE WARRANTY. RETAIN THESE INSTRUCTIONS FOR FUTURE USE.

- WARNING! Danger of serious personal injury exists. Serious personal injury can occur when using a loading ramp.
- Regularly check ramp for worn, loose, or damaged parts. If you find any of these conditions DO NOT USE THE RAMP. Contact your Sealey dealer for repairs. Failure to do so may cause severe injury!
- The surface of the aluminium ramp may become slippery in icy or wet conditions. Caution should be used when using the ramp.
- ✓ Keep the aluminium ramp surface free of dirt and debris.
- Always check the vehicle manufacturer's recommended degree of incline. Do not use ramps at a steeper angle than recommended.
- X DO NOT add to or modify any part of the aluminium ramp. Doing so will void your warranty.
- **X DO NOT** use the aluminium ramp for purposes other than those it was designed for.
- ✓ Use caution when folding and unfolding your aluminium ramp. Beware of pinch points.
- ✓ Be sure that the ramp is always on a solid landing and firmly placed. Always anchor your aluminium ramp in place.
- ✓ Clean aluminium ramps with water and mild detergent.
- WARNING! The warnings, cautions and instructions referred to in this manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator.

□ WARNING! DO NOT EXCEED MAXIMUM CAPACITY OF 200kg

Manufactured from strong durable yet lightweight aluminium. Provides safe and easy ramp access for single/in-line wheeled vehicles. Suitable for loading/unloading motorbikes or wheel barrows from vans or trailers. Features hooks at one end to help secure ramp while in use. Folding design allows compact storage when not in use.

Folded Dimensions (L x W x H):	934 x 296 x 154mm
Extended Dimensions (L x W x H):.	1828 x 296 x 60mm
Maximum Capacity:	200kg
Weight:	
- 5 -	



NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim. INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.

